

FLARE-MINI-AD-PIN

~100° x 20° oval beam. Assembly with location pins.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16 mm
Height	8.6 mm
Fastening	glue, pin
Colour	clear
Box size	
Box weight	0 kg
Quantity in Box	2400 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
FLARE-MINI-AD-PIN	Lens	PMMA	clear



Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

LEDiL

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION: 

DRAWING TITLE

Datasheet FLARE-MINI_PIN

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."

SIZE

PART NUMBER

A4

-

SCALE

2:1

WEIGHT

(g)

SHEET

1/1


PHOTOMETRIC DATA (MEASURED):





LED XB-D
 FWHM 100.0 + 16.0°
 Efficiency 93 %
 Peak intensity 1.200 cd/lm
 Required components:




LED XP-E2
 FWHM 93.0 + 19.0°
 Efficiency 94 %
 Peak intensity 1.300 cd/lm
 Required components:



LED XP-G
 FWHM 100.0 + 20.0°
 Efficiency 94 %
 Peak intensity 1.100 cd/lm
 Required components:





LED XP-G2
 FWHM 97.0 + 24.0°
 Efficiency 94 %
 Peak intensity 1.000 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):





LED XP-L
 FWHM 111.0 + 30.0°
 Efficiency 90 %
 Peak intensity 0.710 cd/lm
 Required components:





LED XP-L2
 FWHM 100.0 + 30.0°
 Efficiency 94 %
 Peak intensity 0.760 cd/lm
 Required components:



LED XT-E
 FWHM 104.0 + 19.0°
 Efficiency 94 %
 Peak intensity 1.100 cd/lm
 Required components:




LED LUXEON CZ
 FWHM 101.0 + 13.0°
 Efficiency 94 %
 Peak intensity 1.600 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):





LED NVSxx19A
FWHM 100.0 + 20.0°
Efficiency 94 %
Peak intensity 1.100 cd/lm
Required components:





LED Oslon Square EC
FWHM 92.0 + 21.0°
Efficiency 94 %
Peak intensity 1.100 cd/lm
Required components:



LED LH351B
FWHM 98.0 + 24.0°
Efficiency 94 %
Peak intensity 1.000 cd/lm
Required components:




LED LH351Z
FWHM 99.0 + 25.0°
Efficiency 94 %
Peak intensity 1.100 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):



LED LUXEON C
FWHM 15.0 + 94.0°
Efficiency 93 %
Peak intensity 1.350 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)