

Product SKU:	C1364.41.90
Product Description:	Speaker Wire, Superflex® [®] , No. of Conductors: 2, Gauge Size (AWG): 12, Conductor/Strands: 7x37/36, Jacket: Premium Grade Clear Superflex® [®] PVC, Temperature Range: -20°C to +60°C - Clear - 1000 Ft. Reel
Product Category:	Electronics - Special Applications - Audio, Video, and Entertainment Cable - Superflex® [®] Speaker Wire - Parallel Construction

**Product Construction:**

Conductor:	12 AWG fully-annealed, stranded bare copper conductor per ASTM B-3
Insulation/Jacket:	- Premium grade clear Superflex®[®] PVC - Temperature range: -20°C to +60°C

Product Specification:

No. of Conductors:	2
Conductor Size (AWG):	12
Conductor/Strands:	7x37/36
Jacket Color:	Clear
Nominal Insulation Thickness (in):	0.060
Nominal Insulation Thickness (mm):	1.52
Nominal Outside Diameter (in):	0.230 x 0.470
Nominal Outside Diameter (mm):	5.84 x 11.94
Standard Packaging:	1000' Non-returnable Wood Reels
Standard Package Quantity:	1

UPC #:	079407762606
Put-up:	1000
SCC-14:	50079407762600
Cube:	960
Weight Per Unit of Measure:	.079
ColorOption:	Clear

Product Information:

Applications:	- Hi-fi and stereo speaker wire - Juke boxes - Lamps - Radios - Suggested voltage rating: 120 Volts - Not for in-wall use
Compliances:	UL Misc. (UL: 120V)
Packaging:	1000' (305 m) Spools 500' (152 m) Spools - Other put-ups available- consult Customer Service

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL
BRAND**