KEMET Part Number: C44PLGR6600ZASJ

C44P, Film, Metallized Polypropylene, AC Filter, 600 uF, 5%, 330 VAC, 700 VDC



General Information	
Series:	C44P
Dielectric:	Metallized Polypropylene
Style:	Can
Features:	Single Phase PFC
RoHS:	Yes
Lead:	Threaded Studs M10
AEC-Q200:	No
Miscellaneous:	Thermal Resistance = 2.4 C/W.

Dimensions	
D	85mm +/-0.5mm
L	280mm +/-2mm
W	21mm +/-1mm
S	35mm +/-1mm

Specifications	
Capacitance:	600 uF
Capacitance Tolerance:	5%
Voltage AC:	330 VAC
Voltage DC:	700 VDC
Temperature Range:	-25/+70°C
Rated Temperature:	70°C
Insulation Resistance:	10 MOhms
Max dV/dt:	12.5 V/us
Resistance:	1.1 mOhms (10kHz)
Ripple Current:	75 Amps (10kHz 40C)
Inductance:	210 nH

Packaging Specifications	
Mounting:	Bolt - M12x16
Packaging:	Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

© 2006 - 2020 KEMET