

EMILY-WWW

~60° wide beam. 13.43 mm high lens.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 26 mm
Height	13.4 mm
Fastening	pin, tape
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	11.2 kg
Quantity in Box	1690 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
EMILY-WWW	Lens	PMMA	clear
SPUTNIK-TAPE	Tape	PU tape	black





PHOTOMETRIC DATA (MEASURED):





LED XHP35 HD
FWHM 70.0°
Efficiency 82 %
Peak intensity 0.710 cd/lm
Required components:





LED XP-E
FWHM 58.0°
Efficiency 86 %
Peak intensity 1.000 cd/lm
Required components:



LED XP-E2
FWHM 69.0°
Efficiency 86 %
Peak intensity 0.770 cd/lm
Required components:




LED XP-G
FWHM 57.0°
Efficiency 86 %
Peak intensity 1.000 cd/lm
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XP-G2
FWHM 61.0°
Efficiency 87 %
Peak intensity 0.900 cd/lm
Required components:





LED XP-G3
FWHM 63.0°
Efficiency 93 %
Peak intensity 0.830 cd/lm
Required components:



LED XP-L
FWHM 69.0°
Efficiency 82 %
Peak intensity 0.680 cd/lm
Required components:




LED XP-L HI
FWHM 66.0°
Efficiency 88 %
Peak intensity 0.820 cd/lm
Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON A
FWHM 57.0°
Efficiency 84 %
Peak intensity 0.900 cd/lm
Required components:





LED NCSxx19B
FWHM 60.0°
Efficiency 83 %
Peak intensity 0.900 cd/lm
Required components:



LED NVSxx19B/NVSxx19C
FWHM 54.0°
Efficiency 85 %
Peak intensity 1.000 cd/lm
Required components:



LED Oslon Square EC
FWHM 61.0°
Efficiency 85 %
Peak intensity 0.900 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)