

CAD32P7TQ

Control relay, TeSys Deca, 3NO+2NC, AC-14/
AC-15, 230 VAC 50/60 Hz Standard coil, bulk
qty



Main

Range	TeSys TeSys Deca
Product name	TeSys CAD TeSys Deca
Product or component type	Auxiliary contactor
Device short name	CAD
Contactor application	Control circuit
Utilisation category	AC-14 AC-15
Control circuit type	AC
Coil type	Standard
Suppressor technology	Without built-in
Pole contact composition	3 NO + 2 NC
[Uc] control circuit voltage	230 V AC 50/60 Hz
Connections - terminals	1 x 1...4 mm ² flexible with cable end 1 x 1...4 mm ² flexible without cable end 1 x 1...4 mm ² solid without cable end 2 x 1...2.5 mm ² flexible with cable end 2 x 1...4 mm ² flexible without cable end 2 x 1...4 mm ² solid without cable end
Quantity per set	Set of 10

Complementary

Contact operation	Mechanically linked conforming to IEC 60947-5-1
Control circuit voltage limits	Drop-out: 0.3...0.6 U _c Operational: 0.8...1.1 U _c at 50 Hz Operational: 0.85...1.1 U _c at 60 Hz
[Ui] rated insulation voltage	600 V - certifications CSA 600 V - certifications UL 690 V - overvoltage category III (pollution degree 3) - conforming to IEC 60947-5-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Tightening torque	1.7 N.m
[Ue] rated operational voltage	<= 690 V AC 25...400 Hz
[Ith] conventional free air thermal current	10 A (at 60 °C)
Irms rated making capacity	140 A at <= 690 V AC conforming to IEC 60947-5-1
Associated fuse rating	10 A gG at <= 690 V conforming to IEC 60947-5-1
Inrush power in VA	70 VA (at 20 °C)
Hold-in power consumption in VA	8 VA 50 Hz (at 20 °C)
Mechanical durability	30000000 cycles
Maximum operating rate	3 cyc/s 20 °C
Operating time	12...22 ms coil energisation and NO closing 4...12 ms coil de-energisation and NO opening 4...19 ms coil energisation and NC opening 6...16 ms coil de-energisation and NC closing
Minimum switching current	5 mA
Minimum switching voltage	17 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Non-overlap time	1.5 Ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Insulation resistance	> 10 MOhm
Height	77 mm
Width	45 mm
Depth	86 mm
Net weight	0.58 kg




Environment

Standards	EN/IEC 60947-5-1 GB/T 14048.5 UL 60947-5-1 CSA C22.2 No 60947-5-1 JIS C8201-5-1
Product certifications	CB Scheme CCC UL CSA EAC CE UKCA
IP degree of protection	IP2X conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-40...70 °C at Uc -5...60 °C at 0.8...1.1 Uc
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating
Shock resistance	10 gn control relay open 15 gn control relay closed
Vibration resistance	2 gn 5...300 Hz control relay open 4 gn 5...300 Hz control relay closed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.000 cm
Package 1 Width	30.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	343.900 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.711 kg
Unit Type of Package 3	P06
Number of Units in Package 3	384
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	140.596 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months