



T1M-07-F-SV-L

T1M-05-F-SH-L



ISS1-10-L



CC09R-01-GF

(1.00 mm) .0394"

ISS1, CC09R, CC09M, T1M SERIES

DISCRETE WIRE COMPONENTS & TOOLING

SPECIFICATIONS

For complete specifications see www.samtec.com?ISS1, www.samtec.com?CC09R or www.samtec.com?CC09M

TOOLING

- Hand tool: CAT-HT-309-2830-12
- Clamp for mounting hand tool to work table: CAT-HT-MNT-01
- Mini Applicator: CAT-MA-309-2830-XX-01

TYPE	NO. OF POSITIONS	LATCH	TYPE	01	PLATING
ISS1 = Single Row Body	-02, -03, -05, -07, -10, -15, -20	(Leave blank for no latch) -L = Positive Latch	CC09R = Contact, Full Reel (30,000 Parts per Reel)	CC09M = Contact, Mini Reel (5,000 Parts per Reel)	-GF = 3 μ" (0.07 μm) Gold contact and tail -T = Tin
<p>No. of positions x (1.00) .03937 + (1.20) .047</p> <p>(1.00) .03937</p> <p>(5.00) .197</p> <p>(4.20) .165</p> <p>LATCH</p>	<p>No. of positions x (1.00) .03937 + (3.00) .118</p> <p>(1.00) .03937</p> <p>(2.10) .083</p> <p>NO LATCH</p> <p>Insulator Material: Natural Nylon</p>		<p>(9.01) .355</p> <p>(2.76) .109</p> <p>(3.60) .141</p> <p>(3.81) .150</p> <p>(3.60) .141</p>		<p>Contact Material: Phosphor Bronze</p>

Mates with: S1SS(T)

SPECIFICATIONS

For complete specifications see www.samtec.com?T1M

- Insulator Material:** Natural LCP
Terminal Material: Phosphor Bronze
Weld Tab: Phosphor Bronze
Plating: Au or Sn over 50 μ" (1.27 μm) Ni
Operating Temp Range: -55 °C to +85 °C
Current Rating (S1SS (28 AWG)/T1M): 3.3 A per pin (1 pin powered)
Voltage Rating: 250 VAC/353 VDC
RoHS Compliant: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



Note: Some lengths, styles and options are non-standard, non-returnable.

T1M	NO. OF POSITIONS	PLATING OPTION	ROW OPTION	LATCH	OPTION
-02, -03, -05, -07, -10, -15, -20	-F = 3 μ" (0.07 μm) Gold on contact, Matte Tin on tail -T = Tin	-SH = Single Row Horizontal -SV = Single Row Vertical	(Required in callout) -L = Positive Latch	-K = (4.00 mm) .157" DIA Polyimide Film Pick & Place Pad (-SH only) -P = Pick & Place Pad (-SV only)	
<p>(0.20) .008</p> <p>(4.25) .167</p> <p>(5.20) .205</p> <p>No. of positions x (1.00) .0394 + (2.40) .094</p> <p>(4.60) .181</p> <p>(1.00) .0394</p> <p>-SH</p>	<p>(1.50) .059</p> <p>(5.10) .201</p> <p>(5.50) .217</p> <p>(4.45) .179</p> <p>(0.20) .008</p> <p>(0.80) .031</p> <p>(3.90) .154</p> <p>-SV</p>				<p>OTHER SOLUTIONS</p> <ul style="list-style-type: none"> • Without latch Contact Samtec.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.