
DESCRIPTION: 9 POS MICRO-D FEMALE (ASSEMBLED) TO BLUNT CUT

THUMBSCREWS: NICKEL PLATED STEEL - UNC #2-56 THREAD



1. P1: NORCOMP p/n 960-009-010R011
2. P2: BLUNT CUT END
3. WIRE: 28AWG [7X36] x9C +ALUMINUM FOIL W/ BRAID 65%, UL2464+CSA, COLOR BLACK
4. PINOUT:

P1		P2
1		BLACK
2		BROWN
3		RED
4		ORANGE
5		YELLOW
6		GREEN
7		BLUE
8		VIOLET
9		GRAY
SHELL		SHIELD

P/N	L±T
CCA-009-F22R152	22ft±4in
CCA-009-I18R152	18±0.590in
CCA-009-I36R152	36±0.787in
CCA-009-I72R152	72±0.984in
CCA-009-M.5R152	500±15mm
CCA-009-M01R152	1000±20mm
CCA-009-M02R152	2000±25mm
CCA-009-M03R152	3000±35mm

NOTE:
NOT DESIGNED TO MATE WITH NORCOMP 580-M // 581-M SERIES CONNECTORS.
IF ANY QUESTIONS PLEASE CONTACT ENG@NORCOMP.NET

PACKAGED: 1 PER BAG

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:	DATE:
P.JENKINS	01/18/2012

NorComp

SCALE:	SHEET	OF	REV
NTS	1	1	7

DWG NO. CCA-009-YYYR152