

# CFSA69383P1-30D43F ✓ ACTIVE

TE Internal #: CFSA69383P1-30D43F

Antenna, Cellular, Building Ceiling, 4.3-10 Female, Cable Length .

98 ft [.3 m], External, Low Profile

[View on TE.com >](#)



## Antennas



Wireless Application: **Cellular**

Mounts To: **Building Ceiling**

Antenna Connector Type: **4.3-10 Female**

Cable Length: **.3 m [.98 ft]**

Antenna Style: **External**

## Features

### Product Type Features

Antenna Connector Type	4.3-10 Female
------------------------	---------------

### Configuration Features

Band Type	AWS-3, DCS, GSM, LTE, UMTS, WiMax
-----------	-----------------------------------

Number of Ports	1
-----------------	---

Antenna Style	External
---------------	----------

Antenna Type	Low Profile
--------------	-------------

### Signal Characteristics

Gain (Max)	5.8 dB
------------	--------

Frequency Band	698 – 806 MHz, 698 – 960 MHz, 824 – 894 MHz, 824 – 894 MHz, 880 – 890 MHz, 1350 – 1550 MHz, 1690 – 1880 MHz, 1690 – 4000 MHz, 1850 – 1990 MHz, 1850 – 1990 MHz, 1910 – 2180 MHz, 2300 – 2500 MHz, 2500 – 2700 MHz, 3300 – 3800 MHz, 3300 – 3800 MHz, 3800 – 4000 MHz
----------------	--

### Mechanical Attachment

Mounts To	Building Ceiling
-----------	------------------

### Dimensions

Cable Length	.3 m [.98 ft]
--------------	---------------

### Operation/Application



Coverage Type	Omnidirectional
---------------	-----------------

**Industry Standards**

Wireless Application	Cellular
----------------------	----------

**Product Compliance**

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

**Product Compliance Disclaimer**

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

**Compatible Parts**

TE Part # CFSA69383P-B30NF  
OMNI,DBAND,30cm,NF OD180MM,  
BULK PACK,16P

TE Part # CFSA69383P1-30NF  
OMNI,DBAND,30cm,NF,HOLES 698-  
960,1690-40

TE Part # CFSA69594P1-30D43F  
OMNI,CEILING,30cm,D43F,

**Customers Also Bought**



## Documents

### Datasheets & Catalog Pages

[Ultra-low Profile/Low PIM Ceiling Mount Antenna 698-960 MHz/1350-1550 MHz/1690-4000 MHz](#)

English

### Agency Approvals

[UK Declaration of Conformity](#)

English