

PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



Products Line

- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke

Product Search

CLH1005-S

Home > Products > Chip Inductor > CLH1005-S



Part Number : CLH1005T-1N0?-S

Structure	Multilayer
Size Code(JIS/EIA)	1005/0402
Inductance	1
Unit	nH
Tolerance(±%)	0.3nH
Test Frequency(L)	100 MHz,200 mV
Q Min	8
Test Frequency(Q)	100 MHz,200 mV
RDC(?)Max	0.07
IDC(mA)Max	400
Operating Temperature	- 5 5 °C ~ 1 2 5 °C(Including self - temperature rise)
L(mm)	1.0±0.10
W(mm)	0.5±0.1
T(mm)	0.5±0.1

1.IDC:Applied the current to coils
the inductance shall be less than 10% initial value.

P/N	CLH1005T-1N0S-S-NP
Part Numbering	
Dimensions	
Packing	
Recommended Pattern	
Electrical Characteristics Curve	
S Parameter	

P/N	CLH1005T-1N0S-S
Part Numbering	
Dimensions	
Packing	
Recommended Pattern	
Electrical Characteristics Curve	
S Parameter	

Back