

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFCLT25FC3 Pr
 - Part Drawings
 - PDFCorrugated L..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'CLT100F-X4'


Your search criteria matched only one product, shown below

CLT100F-X4



Corrugated Loom Tubing is offered for applications where spiral wrap or braided expandable sleeving may be difficult to install or where they do not offer the amount of protection required. This version features a lengthwise slit which makes it easy to install onto a bundle of wires or a pre-assembled harness assembly.

- Protects and reduces the risk of damage to wiring
 - Resistant to crush, impact, and abrasion
 - Slit wall design eases installation
 - Can be held in place using Panduit push mount cable ties or mounts
 - Applications include control panel wiring and cable harness management
- * Order number of reels required.

Part Number	CLT100FX4
RoHS Compliancy Status	Compliant
Part Description	Slit Corrugated Loom Tubing is offered for applications where Spiral Wrap or Braided Expandable Sleeving may be difficult to install or they do not offer the amount of protection required.
Product Type	Slit Wall Corrugated Loom Tubing
Material	Polyethylene
Color	Yellow
CE Compliant	No
Flammability Rating	HB
Inside Diameter (In.)	0.92
Inside Diameter (mm)	23.2
Length Per Reel (ft.)	10
Length Per Reel (m)	3.1
Nominal Diameter / Size	1 inch
Outside Diameter (In.)	1.09
Outside Diameter (mm)	27.7
Pricing Description	Corr. Loom Tubing Slit, 1" (25.4mm) x 10', Yellow
Temperature Range	-40°F – 122°F (-40°C – 50°C)
Type	Slit Wall Corrugated Loom Tubing
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.