

Eaton K-Factor nonlinear ventilated transformer

H29M28F45EE

UPC:786680102356

Dimensions:

- **Height:** 39 IN
- **Length:** 22 IN
- **Width:** 29 IN

Weight:582 LB

Notes:NEMA TP-1 efficient

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Special Features:** Electrostatically shielded
- **Type:** Nonlinear, ventilated transformer
- **Coil Material:** Aluminum
- **Enclosure:** NEMA 2
- **Frame:** 914D
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 208 V
- **Secondary Voltage:** 208 Y/120 V
- **Tap Size:** 2 at +2.5% FCAN, 4 at -2.5% FCBN
- **Temperature Rise:** 115 °C rise
- **Volt Ampere Rating:** 45 kVA
- **Weathershield:** WS39
- **Wiring Connection:** 283A

Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - H29M28F45EE](#)

Certifications:



- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.