

PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



Products Line

- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke
- ◆ **Product Search**

CS1008

Home > Products > Chip Inductor > CS1008



Part Number : CS1008-1R5?-S

Structure	Wire Wound
Size Code(JIS/EIA)	2520/1008
Inductance	1500
Unit	nH
Tolerance(±%)	10,5,2
Test Frequency(L)	7.9MHz
Q Min	28
Test Frequency(Q)	50MHz
SRF(MHz)Min	200
RDC(?)Max	2.3
Irms(mA)Max	330
Operating Temperature	- 4 0℃~ 1 2 5℃(Including self - temperature rise)
L(mm)	2.92Max.
W(mm)	2.79Max.
T(mm)	2.1Max.

- 1.Irms for 15℃ rise above 25℃ ambient.
- 2.L/Q Test OSC @200mV.
- 3.Inductance would be correct Chilisin standard piece.

P/N	CS1008-1R5G-S
Part Numbering	
Dimensions	
Packing	  
Recommended Pattern	
Electrical Characteristics Curve	 

[Back](#)