

# PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



- Power Inductor
  - Chip Inductor
  - Bead
  - Common Mode Choke
  - **Product Search**
- 

CS1008

Home > Products > Chip Inductor > CS1008



## Part Number : CS1008-R22?-S

Structure	Wire Wound
Size Code(JIS/EIA)	2520/1008
Inductance	220
Unit	nH
Tolerance(±%)	10,5,2
Test Frequency(L)	25MHz
Q Min	45
Test Frequency(Q)	100MHz
SRF(MHz)Min	700
RDC(? )Max	0.84
Irms(mA)Max	500
Operating Temperature	- 4 0 °C ~ 1 2 5 °C(Including self - temperature rise)
L(mm)	2.92Max.
W(mm)	2.79Max.
T(mm)	2.1Max.

- 1.Irms for 15°C rise above 25°C ambient.
- 2.L/Q Test OSC @200mV.
- 3.Inductance would be correct Chilisin standard piece.

P/N	CS1008-R22G-S
Part Numbering	
Dimensions	
Packing	   
Recommended Pattern	
Electrical Characteristics Curve	 

[Back](#)