

CS6375



50Amp, 125/250V AC, Non-NEMA, 3P, 4W, Black & White Locking Flanged Inlet, Industrial Grade, Grounding, California-Style(CS) – GRAY METAL

Leviton's Black &White 50 Amp, Non-NEMA line of industrial grade locking blade devices feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts and blades are solid one-piece construction for superior conductivity. Corrosion resistant versions feature nickel plated contacts and blades, plus stainless steel shrouds and screws. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

UPC Code : 078477326312

Country Of Origin : Mexico

Technical Information

Electrical Specifications

Amperage : 50 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Maximum Working Voltage : 125/250V as rated

Pole : 3

Temperature Rise : Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Voltage : 125/250 VAC

Wire : 4

Environmental Specifications

Environment : Dry

Flammability : Rated V-2 per UL94

Operating Temperature : -40°C to 75°C

Material Specifications

Body & Contract Carrier : Reinforced Nylon

Color : Gray Metal

Face Module : Nylon

Flanged Casing : Zinc Plated Steel

Ground Shunt : Bronze

Grounding Shunt Rivet : Brass

Inlet Blade : 0.100inch thick Brass

Terminal Block : 0.062inch thick Copper

Terminal Set Screw : SS 302/304

Mechanical Specifications

Product ID : Ratings and Catalogue No. molded into face

Terminal Accom. : #10 min to #4max AWG Solid or Stranded Wire

Terminal ID : X, W, Y, Z and Green for ground

Product Features

Brand : Black and White

Color : Gray Metal

Device Type : Locking Flanged Inlet

NEMA : Non-NEMA

Standards and Certifications

CSA C22.2 No. 42 : File 152105

NOM : 057

RoHS : Compliant

UL498 : File E13399

Warranty : Lifetime Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

