



Banner's Response to the COVID-19 Pandemic

CSB-M1281M1281

► SPLITTERS



Euro-style Quick Disconnect Splitter Cable
 8 Pin Double-ended with 0.3 Female Branches and
 Male Rotatable Trunk Connector; 0.3 m Trunk
 Length
 8X22 GA 1 Ft Trunk 1 Ft Branch
 Part Number: 73252

SPECIFICATIONS

Number of Contacts	8
Number of Connectors	3
Cable Jacket Material	PVC
Cable Jacket Color	Yellow
Connector Body Material/Color	PUR Black
Outside Cable Diameter (mm)	5.5
Cordset Length (m)	0.6
Trunk Length (m)	0.3
Shield/No Shield	No Shield
Coupling Material/Color	Nickel Plated Brass
Maximum Temp. (°C)	105
Current Rating (A)	4.0

Minimum Temp. (°C)	-40
Voltage Rating (V)	250 V ac/300 V dc
IP Rating	IP67
Primary Connector Type	EURO
Primary Coupling Method	M12 Single Key
Primary Gender	Male
Primary Orientation	Straight
Primary Number of Conductors	8
Primary AWG	22
Splitter Cable Diameter	5.5, 5.5
Splitter Branches: Connector Type	M12F, M12F
Splitter Branches: Coupling Method	M12 Single Key, M12 Single Key
Splitter Branches: Orientation	Straight, Straight
Splitter Branches: Number of Conductors	8, 8
Splitter Branches: AWG	22, 22
Splitter Branches Length (m)	0.3, 0.3
Splitter Function	Parallel
Feature: Hazardous Area	No
Oil/Grease Resistant	No

COMPATIBLE PRODUCTS



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America