



PC card drilling dimensions(after plating)  
(thickness 1.60±0.20mm)

rev	ecn no	dr	date
A	-	BAR	2003/04/17
B	LS05-001	MPE	2005/03/14
C	LS05-0056	MPE	2005/06/30
D	LS06-0097	LGO	2006/07/28
E	I09-0268	NG	2009-11-24
F	I10-0059	NG	2010-02-23

TIN LEAD PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	PART NUMBER
09	30.81	24.99	16.96	16.79	10.96	D09P24A6GX00
15	39.14	33.32	25.18	25.12	19.18	D15P24A6GX00
25	53.03	47.04	39.12	38.84	33.12	D25P24A6GX00
37	69.32	63.50	55.68	55.30	49.68	D37P24A6GX00

LEAD FREE PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	PART NUMBER
09	30.81	24.99	16.96	16.79	10.96	D09P24A6GX00LF
15	39.14	33.32	25.18	25.12	19.18	D15P24A6GX00LF
25	53.03	47.04	39.12	38.84	33.12	D25P24A6GX00LF
37	69.32	63.50	55.68	55.30	49.68	D37P24A6GX00LF

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:  
SEE DRAWING C01-8646-0000

www.fciconnect.com

Dr	LELEON	1992-09-10	ANGULAR	tolerance std	ISO 1302	ISO 406 ISO 1101	projection	mm
Eng	PESSON	1992-09-10	ANGULAR	tolerance std	ISO 1302	ISO 406 ISO 1101	projection	mm
Chr	NIRMAL GEORGE	2010-02-23	0xx' ±2	tolerance std	ISO 1302	ISO 406 ISO 1101	projection	mm
Appr	SUDHIR VARMA	2010-02-23	Product family	tolerance std	ISO 1302	ISO 406 ISO 1101	projection	mm

**FCI** MALE CONNECTOR DELTA D ST  
straight, solder type for

Scale 2

Rev. F

C01-8646-0820

CUSTOMER sheet 1 of 1