






Apr.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Applicable standard					
Rating	Operating Temperature Range	-35 to +85°C (Note1)	Storage Temperature Range	-10 °C to +60°C (Note3)	
	Operating Humidity Range	40% to 80% (Note2)	Storage Humidity Range	40% to 70% (Note3)	
	Voltage	100 V AC/DC	Applicable Connector	DF20%-*DS-1C(##)	
	Current	AWG 28 : 1.0A/pin AWG 30 : 0.9A/pin AWG 32 : 0.7A/pin			Applicable Contact
Specifications					
Item	Test method	Requirements	QT	AT	
<b>Construction</b>					
General Examination	Visually and by measuring instrument.	According to drawing.	X	X	
Marking	Confirmed visually.		X	X	
<b>Electric Characteristics</b>					
Contact Resistance Millivolt Level Method	20mV max, 1mA (DC or 1000Hz).	30 mΩ MAX.	X	—	
Insulation Resistance	100 V DC.	500 MΩ MIN.	X	—	
Voltage Proof	300 V AC for 1 min.	No flashover or breakdown.	X	—	
<b>Mechanical Characteristics</b>					
Mechanical Operation	50 times insertion and extraction.	1) Contact resistance: 30 mΩ MAX. 2) No damage, crack or looseness of parts.	X	—	
Vibration	Frequency 10-55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 directions.	1) No electrical discontinuity of 1 μ s. 2) No damage, crack or looseness of parts.	X	—	
Shock	Acceleration 490 m/s <sup>2</sup> duration of pulse 11 ms at 3 times for 3 directions.	1) No electrical discontinuity of 1 μ s. 2) No damage, crack or looseness of parts.	X	—	
<b>Environmental Characteristics</b>					
Damp Heat (Steady State)	Exposed at 40 ± 2°C, humidity 90-95 %, 96 h. (After leaving the room temperature for 1-2h.)	1) Contact resistance: 30 mΩ MAX. 2) Insulation resistance: 500 MΩ MIN. 3) No damage, crack or looseness of parts.	X	—	
Rapid Change Of Temperature	Temperature -55°C → +85°C Time 30min → 30min Under 5 Cycles. (The transferring time of the tank is 2-3 min) (After leaving the room temperature for 1-2h.)	1) Contact resistance: 30 mΩ MAX. 2) Insulation resistance: 500 MΩ MIN. 3) No damage, crack or looseness of parts.	X	—	
Dry Heat	Exposed at +85±2°C, 96h	1) Contact resistance: 30 mΩ MAX. 2) Insulation resistance: 500 MΩ MIN. 3) No damage, crack or looseness of parts.	X	—	
Cold	Exposed at -55±3°C, 96h	1) Contact resistance: 30 mΩ MAX. 2) Insulation resistance: 500 MΩ MIN. 3) No damage, crack or looseness of parts.	X	—	
Remarks Note 1 : Include the temperature rising by current. Note 2 : No condensing. Note 3 : Apply to the condition of long term storage for unused products before mount on PCB, After mounted on PCB, operating temperature and humidity range is applied for interim storage during transportation.					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
					
Unless otherwise specified, refer to IEC 60512.			APPROVED	HS. OKAWA	20200310
			CHECKED	SZ. ONO	20200310
			DESIGNED	SN. MIWA	20200310
			DRAWN	DS. HIROWATARI	20200306
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC-311790-52-00
	SPECIFICATION SHEET		PART NO.	DF20F-*DP-1H (52)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL686-	 1/2

Specifications					
Item	Test method	Requirements	QT	AT	
Resistance To Soldering Heat	1) Reflow soldering << Reflow time >> Number of reflow cycles : 2 cycles max. Duration above 220°C : 60sec. max. Peak temperature : 250°C, 10sec. max. << Pre-heat time >> Pre-heat temperature : 150-180°C Pre-heat time (min) : 90 sec. Pre-heat time (max) : 120 sec. 2) Manual soldering Soldering iron temperature : 300°C, Soldering time : 3s. No strength on contact.	No deformation of case of excessive looseness of the terminals.	X	—	
Solderability	Soldering temperature : 245°C Duration of immersion : soldering, for 5 sec.	New uniform coating of solder shall cover minimum of 95 % of the surface being immersed.	X	—	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-311790-52-00		
	SPECIFICATION SHEET		PART NO.	DF20F-*DP-1H (52)	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL686-	 2/2