












E3Z-T81-M1J 0.3M

Photoelectric sensor, rectangular housing, infrared LED, through-beam, 15 m, PNP, Light-ON/Dark-ON, M12 pigtail connector, 0.3 m

Specifications

Shape	Cuboid
Sensing method	Through-beam
Sensing distance	15000 mm
Setting method	Manual adjustment
Connection method	M12 pigtail connector
Cable length	0.3 m
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	20 mm
Type of light	Infrared light
Power supply voltage	12-24 V
Degree of protection (IP)	IP67

	E39-L104	Mounting bracket for E3Z sensor, standard, vertical mounting
	E39-L142	Mounting Bracket, protective side wall (for E3Z)
	E39-L144	Sensor mounting Bracket, Protective bracket for E3Z pre-wired
	E39-L153	Mounting bracket for E3Z sensor, L shape, for prewired
	E39-L43	Mounting bracket for E3Z sensor, side mounting
	E39-L98	Protective metal cover for E3S-A/E3Z vertical sensor
	E39-S65A	Slit for E3Z-T, 0.5mm diameter
	E39-S65B	Slit for E3Z-T, 1mm diameter
	E39-S65C	Slit for E3Z-T, 2mm diameter
	E39-S65E	Slit for E3Z-T, 1x10mm diameter

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3Z Brochure

EN PDF 1.34 MB



E3Z Compact Photoelectric Sensor with Built-in Amplifier Datasheet

EN PDF 3.13 MB




EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Omron Product REACH SVHC Information Technical Information

EN PDF 767 KB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 27 June, 2024. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU