



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| D | 8mm +/-0.5mm |
| L | 10.2mm +/-0.3mm |
| W | 0.9mm +/-0.2mm |
| F | 0.3mm MAX |
| A | 8.3mm +/-0.2mm |
| B | 8.3mm +/-0.2mm |
| C | 10mm MAX |
| E | 3.4mm +/-0.2mm |
| G | 0.7mm +/-0.2mm |
| P | 3.1mm +/-0.2mm |

Packaging Specifications

Packaging T&R, 380mm

| General Information | |
|---------------------|--------------------------------------|
| Series | EXV |
| Dielectric | Aluminum Electrolytic |
| Style | SMD Can |
| Description | Surface Mount, Aluminum Electrolytic |
| RoHS | Yes |
| Lead | V-Chip |
| AEC-Q200 | No |

| Specifications | |
|---------------------------------|--|
| Capacitance | 330 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 16 VDC, 20 VDC (Surge) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 105°C |
| Life | 5000 Hrs |
| Dissipation Factor | 16% |
| ESR | 0.16 Ohms (100kHz 20C) |
| Impedance | 160 mOhms |
| Ripple Current | 600 mAmps (100kHz 105C), 420 mAmps (120Hz 85C) |
| Compare Ripple Current at 120Hz | 0.42 |
| Leakage Current | 52.8 uA (2min 20°C) |
| Impedance Ratio at -25C | 2 |
| Impedance Ratio at -40C | 3 |
| High Temperature Solder | true |