

PHE426HB6330JR06

aka F426BG334J250C PHE426HB6330JB15R06

Capacitor, film, 0.33 uF, +/-5% Tol, -55/+105C, General Purpose, 250V@85C, Lead Spacing=15 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|------------------------------|--|
| L | 18 | max | Brand: | Rifa |
| H | 12 | max | Capacitance: | 0.33 uF |
| T | 6 | max | Temperature Range: | -55/+105C |
| S | 15 | +/-0.4 | Rated Temperature: | 85C |
| LL | 6 | nom | Voltage @ rated temp: | 250V |
| F | 0.8 | nom | Voltage AC: | 160VAC |
| | | | Tolerance: | +/-5% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | General Purpose |
| | | | Sub Application: | Pulse |
| | | | Dissipation Factor @ 1 kHz: | 0.05% |
| | | | Dissipation Factor @ 10 kHz: | 0.1% |
| | | | Insulation Resistance: | 100 GOhm |
| | | | Inductance: | 6 nH |
| | | | Maximum dVdT: | 120v/us |
| | | | Miscellaneous Electrical: | IEC 60384-16, 1.1; Rthha [85C/2.m/s] = 83 C/W series(PHE426) |
| | | | Package Kind: | Bulk |
| | | | Package Quantity: | 1000 |