

# MMK5183K100J01L16.5TA18

aka F601JF183K100R MMK5183K100J01L16,5TA18

Capacitor, film, 0.018 uF, +/-10% Tol, -55/+100C, General Purpose, 100V@85C, Lead Spacing=5 mm



## Dimensions (mm)

## Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	7.2	max	Brand:	Evox
H	6.5	max	Capacitance:	0.018 uF
T	2.5	max	Temperature Range:	-55/+100C
S	5	+/-0.4	Rated Temperature:	85C
LL	16.5	nom	Voltage @ rated temp:	100V
F	0.5	nom	Voltage AC:	63VAC
			Tolerance:	+/-10%
			Body Type:	Radial Box
			Construction:	Wound
			Application:	General Purpose
			Dissipation Factor @ 1 kHz:	0.8%
			Dissipation Factor @ 10 kHz:	1.2%
			Dissipation Factor @ 100kHz:	2.5%
			Insulation Resistance:	15 GOhm
			Inductance:	6 nH
			Maximum dVdT:	30v/us
			Miscellaneous Electrical:	CECC 30401-042, IEC 60384-2, DIN 44122 series(MMK)
			Package Kind:	Ammo
			Package Quantity:	5000