

MMK7.5154K100K01L16.5TR18

aka F601KG154K100L MMK7,5154K100K01L16,5TR18

Capacitor, film, 0.15 uF, +/-10% Tol, -55/+100C, General Purpose, 100V@85C, Lead Spacing=7.5 mm



Dimensions (mm)

Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	10	max	Brand:	Evox
H	8	max	Capacitance:	0.15 uF
T	4	max	Temperature Range:	-55/+100C
S	7.5	+/-0.4	Rated Temperature:	85C
LL	16.5	nom	Voltage @ rated temp:	100V
F	0.6	nom	Voltage AC:	63VAC
			Tolerance:	+/-10%
			Body Type:	Radial Box
			Construction:	Wound
			Application:	General Purpose
			Dissipation Factor @ 1 kHz:	0.8%
			Dissipation Factor @ 10 kHz:	1.5%
			Insulation Resistance:	15 GOhm
			Inductance:	6 nH
			Maximum dVdT:	20v/us
			Miscellaneous Electrical:	CECC 30401-042, IEC 60384-2, DIN 44122 series(MMK)
			Package Kind:	T&R
			Package Size:	360mm
			Package Quantity:	1700