

# PHE845VF6150MR06L2

aka F845FG154M760C PHE845VF6150MF12R06L2

Capacitor, film, 0.15 uF, +/-20% Tol, -40/+105C, Safety: X1, 760VAC,  
Lead Spacing=27.5 mm



## Dimensions (mm)

## Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	31.5	max	Brand:	Rifa
H	22.5	max	Capacitance:	0.15 uF
T	11.5	max	Temperature Range:	-40/+105C
S	27.5	+/-0.4	Rated Temperature:	105C
LL	6	nom	Voltage @ rated temp:	1500V
F	0.8	nom	Voltage AC:	760VAC
			Tolerance:	+/-20%
			Body Type:	Radial Box
			Construction:	Wound
			Application:	Safety: X1
			Dissipation Factor @ 1 kHz:	0.1%
			Dissipation Factor @ 10 kHz:	0.4%
			Insulation Resistance:	30 GOhm
			Maximum dVdT:	100v/us
			UL_1283:	600V
			IEC_60384-14:	760V
			EN_132400:	760V
			C_22.2_NO.8:	600V
			Miscellaneous Electrical:	PHE845
			Package Kind:	Bulk
			Package Type:	Tray
			Package Quantity:	198