

PC BOARD MOUNTING CONNECTORS

720 SERIES (CRIMP TYPE CONNECTORS)

■ FEATURES


The 720 series connectors (crimp connector) are designed for a wide range of uses, and come in many shapes, two contact arrangements (one and two rows), and various pin types. The 720 series headers can be mated with 700 and 740 series sockets, and are lockable when a special cover is used. Female contacts are secured in the housing by a unique internal spring structure. High-pressure contacts are also available which prevent accidental disconnection in applications that use only a few contacts.

For W and S type headers, insulation molds can be cut to the necessary size.

■ SPECIFICATIONS

Item		Specification
Operating temperature range		-55°C to +85°C
Current rating		DC 3 A
Voltage rating		AC 250 V
Contact resistance		20 mΩ max. (DC 6 V, 0.1 A)
Insulation resistance		1000 MΩ max. (DC 500 V)
Dielectric strength		AC 500 V for 1 minute
Insertion force	Standard contacts	1.05 kg max. (3 pins), 25.2 kg max. (72 pins)
	High-pressure contacts	2.1 kg max. (3 pins), 50.4 kg max. (72 pins)
Withdrawal force	Standard contacts	0.09 kg min. (3 pins), 2.16 kg min. (72 pins)
	High-pressure contacts	0.18 kg min. (3 pins), 4.32 kg min. (72 pins)
Applicable wire		Wire-wrap: AWG #26 to #30 (solid) Crimping: AWG #20 to #32
Applicable PC board (standard)		1.6 mm (0.062 in.)

Note: For thin wire crimping, the crimp height must be adjusted for increased reliability. Please contact us for further information.



■ MATERIALS

Item		Materials
Insulating material	Header	Polyester (UL94V-0)
	Socket	PPO (UL94V-1)
	Cover	Nylon 6 (UL94V-2)
Conductor		Copper alloy
Plating	Contact	Gold
	Terminal	Palladium

Note: Tin-plated connectors are also available for 8- to 34-pin types.


■ MATERIALS (SMT CONNECTOR)

Item		Materials
Insulating material		66 Nylon (UL94V-0)
Conductor		Copper alloy
Plating	Contact	Gold
	Terminal	Palladium

720 Series (Crimp Type Connectors)

CRIMP SOCKET HOUSING (2-ROW, BUMP TYPE)

■ DIMENSIONS



■ PART NUMBERS AND DIMENSIONS

Number of contacts	Part number	Dimensions (unit: mm (in.))	
		A	B
10	FCN-723B010/2	12.70 (0.500)	10.16 (0.400)
14	FCN-723B014/2	17.78 (0.700)	15.24 (0.600)
16	FCN-723B016/2	20.32 (0.800)	17.78 (0.700)
20	FCN-723B020/2	25.40 (1.000)	22.86 (0.900)
26	FCN-723B026/2	33.02 (1.300)	30.48 (1.200)
30	FCN-723B030/2	38.10 (1.500)	35.56 (1.400)
34	FCN-723B034/2	43.18 (1.700)	40.64 (1.600)
40	FCN-723B040/2	50.80 (2.000)	48.26 (1.900)
50	FCN-723B050/2	63.50 (2.500)	60.96 (2.400)
60	FCN-723B060/2	76.20 (3.000)	73.66 (2.900)

■ REMARKS

- A cover may be used.
Part numbers for the cover:
FCN-720C □□□/2S (for 16-, 20-, 26-, 34-, and 50-contact types)
FCN-720C □□□/2P (for 34-, 40-, 50-, and 60-contact types)
FCN-720C □□□/2E (for 20-, 26-, 34-, 40-, 50-, and 60-contact types)


720 Series (Crimp Type Connectors)

CRIMP CONTACT

■ DIMENSIONS

1. Parts in bulk

Tool: Hand crimping tool




Wire gauge (AWG#)	Applied contact	
	Standard type	High pressure
#20	FCN-723J-AU/U	FCN-723J-AU/W
#22		
#24	FCN-723J-AU/Q	FCN-723J-AU/S
#26		
#28		
#30		
#32		

Unit: mm (in.)

2. Parts in strips

Tool: Semiautomatic crimping tool



Wire gauge (AWG#)	Applied contact	
	Standard type	High pressure
#20	FCN-723J-AU/V	FCN-723J-AU/X
#22		
#24	FCN-723J-AU/R	FCN-723J-AU/T
#26		
#28		
#30		
#32		


Unit: mm (in.)

720 Series (Crimp Type Connectors)

CRIMPING TOOLS

■ NOTES ON USING CRIMPING TOOLS

- Many crimping tools are available, but they are not compatible. Always use the crimping tools specified by Fujitsu.
- When using the tools, be sure to adjust the crimp height according to the table below. Otherwise, wires may be loose or break off.



Semiautomatic crimping tool



Hand crimping tool

■ HAND CRIMPING TOOL

Wire gauge (AWG#)	Wire cross-sectional area (mm (in.))	Crimp height (mm (in.))	Insulator diameter (mm (in.))	Hand crimping tool	Contact type		Stripped length (mm (in.))
					Standard type	High pressure	
#20	0.52 to 0.64 (0.0205 to .0251)	0.75 to 0.85 (0.029 to 0.033)	φ1.3 to φ1.8 (0.051 to 0.071)	FCN-723T-T018/H	FCN-723J-AU/U	FCN-723J-AU/W	3.1 to 3.6 (0.122 to 0.141)
#22	0.30 to 0.40 (0.0118 to 0.0157)	0.70 to 0.80 (.027 to .031)					
#24	0.20 to 0.24 (0.0079 to 0.0094)	0.70 to 0.80 (.027 to .031)	φ1.1 to φ1.6 (0.043 to 0.063)	FCN-723T-T007/H	FCN-723J-AU/Q	FCN-723J-AU/S	
#26	0.13 to 0.16 (0.0051 to 0.0063)	0.66 to 0.76 (.026 to .030)					
#28	0.088 to 0.096 (0.0035 to 0.0038)	0.60 to 0.68 (.024 to .027)					
#30	0.055 to 0.060 (0.0022 to 0.0029)	0.68 to 0.75 (.027 to .029)	φ0.7 to φ1.0 (0.028 to 0.039) (φ0.5 to φ0.6) (0.020 to 0.024)	FCN-723T-T008/H (FCN-723T-T015/H)			
#32	0.032 to 0.038 (0.0013 to 0.0015)	0.66 to 0.71 (.026 to .028)					

Note: Also, hand tool is available that can crimp two wires (AWG #30 φ0.5 mm) on one contact.
Part Number: FCN-723T-T014/H, Applicable contact: FCN-723J-Au/Q or S

■ SEMIAUTOMATIC CRIMPING TOOL

Wire gauge (AWG#)	Wire cross-sectional area (mm (in.))	Crimp height (mm (in.))	Insulator diameter (mm (in.))	Semiautomatic crimping tool		Contact type		Stripped length (mm (in.))
				Press	Applicator	Standard type	High pressure	
#20	0.52 to 0.64 (0.0205 to .0251)	0.75 to 0.85 (0.029 to 0.033)	φ1.3 to φ1.7 (0.051 to 0.070)	FCN-M110	FCN-A118	FCN-723J-AU/V	FCN-723J-AU/X	3.1 to 3.6 (0.122 to 0.141)
#22	0.30 to 0.40 (0.0118 to 0.0157)	0.70 to 0.80 (.027 to .031)						
#24	0.20 to 0.24 (0.0079 to 0.0094)	0.70 to 0.80 (.027 to .031)						
#26	0.13 to 0.16 (0.0051 to 0.0063)	0.66 to 0.76 (.026 to .030)	φ0.8 to φ1.6 (0.031 to 0.063)	FCN-A107	FCN-723J-AU/R	FCN-723J-AU/T		
#28	0.088 to 0.096 (0.0035 to 0.0038)	0.60 to 0.68 (.024 to .027)						
#30	0.055 to 0.060 (0.0022 to 0.0029)	0.68 to 0.75 (.027 to .029)	φ0.5 to φ1.3 (0.020 to 0.051)	FCN-A108				
#32	0.032 to 0.038 (0.0013 to 0.0015)	0.66 to 0.71 (.026 to .028)						

Note: FCN-M100 conventional 3-ton press is also available. Contact us.

■ UNITS OF ORDERING PARTS IN STRIPS


Part number	Units of order
FCN-723J-AU/V	5,000
FCN-723J-AU/R	8,000
FCN-723J-AU/X	5,000
FCN-723J-AU/T	8,000

720 Series (Crimp Type Connectors)

POLARIZING KEY

■ DIMENSIONS

Part number: FCN-700A1



■ SPECIFICATION OF POLARITY TO PREVENT INCORRECT INSERTION

	Header	Socket
Polarization	Do one of the following: (1) Cut the contact of a specified pin. (2) Pull out a specified pin.	Plug in a polarizing key in a specified position.
Specification	Specify a two-digit pin number with polarity at the end of the part number. Example: When specifying pin No. 4 FCN-725P050-AU/0#04	Specify a two-digit pin number with polarity at the end of the part number. Example: When specifying pin No. 4 FCN-723J050-AU/2#04

Note: The standard specification is #04 or the end pin number (if the end pin is 50, the specification is #50).

Fujitsu Takamisawa International Headquarter Offices

www.fujitsu.takamisawa.com

Japan

Fujitsu Takamisawa Component Limited
Global Marketing and Sales
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626

North and South America

Fujitsu Takamisawa America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970

Europe

Fujitsu Takamisawa Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950

Asia Pacific

Fujitsu Takamisawa Asia Pacific Pte. Ltd.
102E Pasir Panjang Road
#04-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 375-8560
Fax: (65) 273-3021