

Eaton Series C molded case switch

FD3225KW

UPC:786679040669

Dimensions:

- **Height:** 4.13 IN
- **Length:** 3.38 IN
- **Width:** 4.13 IN

Weight:4.5 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Molded case switch
- **Amperage Rating:** 225A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 35 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** FD
- **Frame Size:** F-frame
- **Series:** Series C
- **Terminals:** Without terminals
- **Frequency Rating:** 50-60 Hz

Supporting documents:

- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [StrandAble terminals product aid](#)

- Power metering and monitoring with Modbus RTU product aid
- MOEM MCCB Product Selection Guide
- Circuit breaker motor operators product aid
- Motor protection circuit breakers product aid
- Current limiting Series C molded case circuit breakers product aid
- Multi-wire lugs product aid
- Plug-in adapters for molded case circuit breakers product aid
- Eatons Volume 4-Circuit Protection
- Molded case circuit breakers
- Time Current Curves for Series C® F-Frame Circuit Breakers
- Installation Instructions for EHD, EDB, EDS, ED, EDH, EDC, FDB, FD, HFD, FDC, HFDDC Circuit Breakers and Molded Case Switches
- Breaker service centers
- Counterfeit and Gray Market Awareness Guide
- MOEM MCCB product selection guide
- Series C J-Frame molded case circuit breakers time current curves
- Series C F-Frame molded case circuit breakers
- Series C G-Frame molded case circuit breakers time current curves
- Eaton Specification Sheet - FD3225KW

Certifications:

- UL Listed

Product compliance: No Data