

# FFPF08S60ST

## 8 A, 600 V, STEALTH II Diode

### Description

The FFPF08S60S is STEALTH™ II diode with soft recovery characteristics. It is silicon nitride passivated ion-implanted epitaxial planar construction.

This device is intended for use as freewheeling of boost diode in switching power supplies and other power switching applications. Their low stored charge and hyperfast soft recovery minimize ringing and electrical noise in many power switching circuits reducing power loss in the switching transistors.

### Features

- Stealth Recovery  $t_{rr} = 30$  ns (@  $I_F = 8$  A)
  - ◆ Max Forward Voltage,  $V_F = 3.4$  V (@  $T_C = 25^\circ\text{C}$ )
- 600 V Reverse Voltage and High Reliability
- This Device is Pb-Free and are RoHS Compliant

### Applications

- General Purpose
- SMPS
- Boost Diode in Continuous Mode Power Factor Corrections
- Power Switching Circuits

### ABSOLUTE MAXIMUM RATINGS $T_C = 25^\circ\text{C}$ unless otherwise noted



Symbol	Parameter	Value	Unit
$V_{RRM}$	Peak Repetitive Reverse Voltage	600	V
$V_{RWM}$	Working Peak Reverse Voltage	600	V
$V_R$	DC Blocking Voltage	600	V
$I_{F(AV)}$	Average Rectified Forward Current @ $T_C = 95^\circ\text{C}$	8	A
$I_{FSM}$	Non-repetitive Peak Surge Current 60Hz Single Half-Sine Wave	80	A
$T_J, T_{STG}$	Operating Junction and Storage Temperature	- 65 to +175	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)



TO-220F-2L  
CASE 221AS

### MARKING DIAGRAM



\$Y = ON Semiconductor Logo  
&Z&3 = Data Code (Year & Week)  
&K = Lot  
F08S60ST = Specific Device Code

### ORDERING INFORMATION

Device	Package	Shipping
FFPF08S60STTU	TO-220F-2L	50 / Tube

# FFPF08S60ST

## THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Maximum Thermal Resistance, Junction-to-Case	3.4	$^{\circ}\text{C}/\text{W}$

## ELECTRICAL CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max	Unit
$V_{F1}$	$I_F = 8 \text{ A}$ $I_F = 8 \text{ A}$ $T_C = 25^{\circ}\text{C}$ $T_C = 125^{\circ}\text{C}$	-	2.1 1.6	2.6 -	V V
$I_{R1}$	$V_R = 600 \text{ V}$ $V_R = 600 \text{ V}$ $T_C = 25^{\circ}\text{C}$ $T_C = 125^{\circ}\text{C}$	-	-	100 500	$\mu\text{A}$ $\mu\text{A}$
$t_{rr}$	$I_F = 1 \text{ A}$ , $di_F/dt = 100 \text{ A}/\mu\text{s}$ , $V_R = 30 \text{ V}$ $T_C = 25^{\circ}\text{C}$	-	-	25	ns
$T_{rr}$ $I_{rr}$ S factor $Q_{rr}$	$I_F = 8 \text{ A}$ , $di_F/dt = 200 \text{ A}/\mu\text{s}$ , $V_R = 390 \text{ V}$ $T_C = 25^{\circ}\text{C}$	-	19 2.2 0.6 21	30 - - -	ns A - nC
$t_{rr}$ $I_{rr}$ S factor	$I_F = 8 \text{ A}$ , $di_F/dt = 200 \text{ A}/\mu\text{s}$ , $V_R = 390 \text{ V}$ $T_C = 125^{\circ}\text{C}$	-	58 4.3 1.3 125	- - - -	ns A - nC
$W_{AVL}$	Avalanche Energy ( $L = 40 \text{ mH}$ )	20	-	-	mJ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pulse: Test Pulse width = 300  $\mu\text{s}$ , Duty Cycle = 2%

## Test Circuit and Waveforms




Figure 1. Diode Reverse Recovery Test Circuit & Waveform




Figure 2. Unclamped Inductive Switching Test Circuit & Waveform

# FFPF08S60ST

## TYPICAL PERFORMANCE CHARACTERISTICS

$T_c = 25^\circ\text{C}$  unless otherwise noted




Figure 3. Typical Forward Voltage Drop




Figure 4. Typical Reverse Current




Figure 5. Typical Junction Capacitance




Figure 6. Typical Reverse Recovery Time




Figure 7. Typical Reverse Recovery Current





Figure 8. Forward Current Deration Curve

**MECHANICAL CASE OUTLINE**  
**PACKAGE DIMENSIONS**




TO-220 Fullpack, 2-Lead / TO-220F-2FS  
CASE 221AS  
ISSUE 0

DATE 29 FEB 2012



<b>DOCUMENT NUMBER:</b>	<b>98AON67438E</b>	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
<b>STATUS:</b>	<b>ON SEMICONDUCTOR STANDARD</b>	
<b>NEW STANDARD:</b>		
<b>DESCRIPTION:</b>	<b>TO-220 FULLPACK, 2-LEAD / TO-220F-2FS</b>	<b>PAGE 1 OF 2</b>



ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative