



### Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Thermal-magnetic
Breaking capacity code	H

### Complementary

Line Rated Current	100 A
Poles description	3P
Breaking capacity	65 kA at 240 V AC 18 kA at 600 V AC 10 kA at 250 V DC 25 kA at 480 V AC
System Voltage	250 V DC 600 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 14...AWG 1/0 (copper) 1 cable(s) AWG 12...AWG 1/0 (aluminium) 1 cable(s)
Terminal identifier	AL100FA
Magnetic hold current	900 A
Magnetic tripping current	1700 A
Phase connection	ABC
Height	6.4 in
Width	4.5 in
Depth	4.13 in

### Environment

product certifications	CSA UL listed
------------------------	------------------

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1304 - Schneider Electric declaration of conformity	Compliant - since 1304 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.