

VIOLET-12X1-RS

~14° wide beam

TECHNICAL SPECIFICATIONS:

Dimensions	294.8 x 41.6 mm
Height	8.8 mm
Fastening	screw
Ingress protection classes	IP66, IP67
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
VIOLET-12X1-RS	Multi-lens	Silicone	clear	
VIOLET-12X1-FRAME	Accessory	Stainless steel	metal	



ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
FN17810_VIOLET-12X1-RS » Box size: 398 x 298 x 150 mm	Multi-lens	78	26	26	8.0



See also our general installation guide: www.ledil.com/installation_guide

PHOTOMETRIC DATA (MEASURED):



LED LIGHT ENGINE VIOLET UVC 281x19.2mm (KL265-50V-SM-WD)
FWHM 18.0°
Efficiency 64 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

Crystal[®]IS

LED KL265-50V-SM-WD
FWHM 18.0°
Efficiency 64 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %



LED LTPL-G35UV275GC-E
FWHM 15.0°
Efficiency 67 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %



LED LTPL-G35UV275GR-E
FWHM 16.0°
Efficiency 66 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

PHOTOMETRIC DATA (MEASURED):

LITEON

LED LTPL-G35UVC275GH
FWHM 18.0°
Efficiency 65 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

LITEON

LED LTPL-G35UVC275GZ
FWHM 18.0°
Efficiency 64 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

LUMINUS

LED XBT-3535-UV
FWHM 12.0°
Efficiency 68 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

LUMINUS

LED XST-3535-UV
FWHM 23.0°
Efficiency 62 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

PHOTOMETRIC DATA (MEASURED):



LED NCSU334B
FWHM 17.0°
Efficiency 66 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %



SEOUL SEMICONDUCTOR

LED CUD7GF1B
FWHM 18.0°
Efficiency 62 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %



SEOUL SEMICONDUCTOR

LED CUD7QF1A
FWHM 17.0°
Efficiency 59 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %



SEOUL SEMICONDUCTOR

LED XMD-FBC-LLCA
FWHM 16.0°
Efficiency 55 %
LEDs/each optic 1
Light colour UV-C
Required components:

The UVC LED result tolerance is ± 10 %

PHOTOMETRIC DATA (MEASURED):

SEOL SEMICONDUCTOR	
LED	XMD-FBC-LLOA
FWHM	31.0°
Efficiency	67 %
LEDs/each optic	2
Light colour	UV-C
Required components:	
The UVC LED result tolerance is ± 10 %	


SEOL SEMICONDUCTOR	
LED	XMD-FBC-LLVA
FWHM	31.0°
Efficiency	63 %
LEDs/each optic	4
Light colour	UV-C
Required components:	
The UVC LED result tolerance is ± 10 %	

PHOTOMETRIC DATA (SIMULATED):




LED XBT-3535-UV
 FWHM 10.0°
 Efficiency 80 %
 LEDs/each optic 1
 Light colour UV-C
 Required components:

The UVC LED result tolerance is ± 10 %




LED NCSU334A
 FWHM 13.0°
 Efficiency 80 %
 LEDs/each optic 1
 Light colour UV-C
 Required components:

The UVC LED result tolerance is ± 10 %




LED NCSU334B
 FWHM 8.0°
 Efficiency 79 %
 LEDs/each optic 1
 Light colour UV-C
 Required components:

The UVC LED result tolerance is ± 10 %



LED WICOP DY9560-27
 FWHM 22.0°
 Efficiency 72 %
 LEDs/each optic 4
 Light colour UV-C
 Required components:

The UVC LED result tolerance is ± 10 %



PHOTOMETRIC DATA (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)