

## LISA2-W-PIN

~35° wide beam. 6.8 mm high variant with location pin installation.


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 9.9 mm
Height	6.8 mm
Fastening	glue, pin
Colour	black
Box size	
Box weight	1.4 kg
Quantity in Box	2000 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
LISA2-W	Lens	PMMA	clear
LISA2-HLD-PIN	Holder	PC	black



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	F10989	LISA2-HLD-PIN	PC	black
2	-	LISA2_lens	PMMA	

Tolerances if not otherwise shown  
According to DIN ISO 2768-1  
Linear measures:  
up to 30mm class M, otherwise class C  
According to DIN ISO 2768-2  
Form and position: class L



Ledil Oy  
Salorankatu 10  
FIN 24240 SALO  
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE  
**Lisa2-PIN-XP assembly**

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE	PART NUMBER
A4	-

SCALE	4:1	WEIGHT	0,5 g	SHEET	1/1
-------	-----	--------	-------	-------	-----



### PHOTOMETRIC DATA (MEASURED):

#### CREE

LED XB-D  
FWHM 32.0°  
Efficiency 86 %  
Peak intensity 1.930 cd/lm  
Required components:


#### CREE

LED XD16  
FWHM 37.0°  
Efficiency 77 %  
Peak intensity 1.700 cd/lm  
Required components:



#### CREE

LED XP-E  
FWHM 37.0°  
Efficiency 90 %  
Peak intensity 1.960 cd/lm  
Required components:



#### CREE

LED XP-G  
FWHM 48.0°  
Efficiency 92 %  
Peak intensity cd/lm  
Required components:

### PHOTOMETRIC DATA (MEASURED):



#### LUMILEDS

LED LUXEON A  
FWHM 46.0°  
Efficiency 88 %  
Peak intensity 1.200 cd/lm  
Required components:



#### LUMILEDS

LED LUXEON C  
FWHM 34.0°  
Efficiency 88 %  
Peak intensity 2.100 cd/lm  
Required components:




#### LUMILEDS

LED LUXEON Rebel ES  
FWHM 46.0°  
Efficiency 93 %  
Peak intensity cd/lm  
Required components:

#### LUMILEDS



LED LUXEON Z  
FWHM 27.0°  
Efficiency 87 %  
Peak intensity 2.860 cd/lm  
Required components:



### PHOTOMETRIC DATA (MEASURED):


#### LUMILEDS

LED LUXEON Z ES  
FWHM 35.0°  
Efficiency 87 %  
Peak intensity 2.100 cd/lm  
Required components:



#### SAMSUNG

LED LH181B  
FWHM 36.0°  
Efficiency 80 %  
Peak intensity 1.800 cd/lm  
Required components:



#### SHARP

LED Double Dome (GM2BB)  
FWHM 44.0°  
Efficiency 88 %  
Peak intensity cd/lm  
Required components:


### PHOTOMETRIC DATA (SIMULATED):



LED XQ-E  
FWHM 49.0°  
Efficiency 90 %  
Peak intensity 1.250 cd/lm  
Required components:



LED XQ-E HI  
FWHM 23.0°  
Efficiency 89 %  
Peak intensity 3.600 cd/lm  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)