

LISA2-O-PIN

~45° x 20° oval beam. 6.8 mm high variant with location pin installation.


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 9.9 mm
Height	6.8 mm
Fastening	glue, pin
Colour	black
Box size	
Box weight	1.4 kg
Quantity in Box	2000 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
LISA2-O-XP	Lens	PMMA	clear
LISA2-HLD-PIN	Holder	PC	black




PHOTOMETRIC DATA (MEASURED):



LED XD16
FWHM 50.0 + 20.0°
Efficiency 66 %
Peak intensity 1.600 cd/lm
Required components:





LED XP-E
FWHM 18.0 + 48.0°
Efficiency 83 %
Peak intensity 2.300 cd/lm
Required components:



LED XP-G
FWHM 46.0 + 24.0°
Efficiency 86 %
Peak intensity cd/lm
Required components:



LED XP-G3
FWHM 47.0 + 26.0°
Efficiency 69 %
Peak intensity 1.300 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



CREE 

LED XQ-E HI
FWHM 15.0 + 50.0°
Efficiency 74 %
Peak intensity 2.730 cd/lm
Required components:





LUMILEDS 

LED LUXEON C
FWHM 50.0 + 17.0°
Efficiency 81 %
Peak intensity 2.500 cd/lm
Required components:



LUMILEDS 

LED LUXEON Z ES
FWHM 50.0 + 19.0°
Efficiency 79 %
Peak intensity 2.300 cd/lm
Required components:



SHARP

LED Double Dome (GM2BB)
FWHM 10.0 + 32.0°
Efficiency %
Peak intensity cd/lm
Required components:

PHOTOMETRIC DATA (SIMULATED):

CREE 

LED	XQ-E
FWHM	13.0 + 40.0°
Efficiency	86 %
Peak intensity	3.500 cd/lm

Required components:

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

www.ledil.com/where_to_buy

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

www.ledil.com/where_to_buy