

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFInsulated Fe..
 - Specification Sheets
 - PDFFerrules wit ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'FSDXL80-12-C'

Your search criteria matched only one product, shown below

FSDXL80-12-C



- Wide sleeve provides a barrier against electrical shorts
- Inside diameter of sleeve suitable for wire with very thick insulation
- Meets DIN dimensional and color standards for single wire containment
- Funnel entry for faster insertion and lower installed cost
- Designed with a seamless barrel to contain loose wire strands for superior terminations
- Eases insertion of stranded wire into terminal blocks
- Multiple pin lengths available

| | |
|-------------------------------|--|
| Part Number | FSDXL80-12-C |
| RoHS Compliancy Status | Compliant |
| Part Description | Polypropylene insulated ferrules – single wire DIN expanded short circuit protection end sleeve. |
| Color | Blue |
| Length (In.) | 0.85 |
| Length (mm) | 21.5 |
| CE Compliant | No |
| Inside Diameter (In.) | 0.09 |
| Inside Diameter (mm) | 2.3 |
| Insulation | Polypropylene |
| Max. Wire Insul. Dia. (In.) | 0.31 |
| Outside Diameter (In.) | 0.10 |
| Outside Diameter (mm) | 2.6 |
| Pin Length (In.) | 0.47 |
| Pin Length (mm) | 12.0 |
| Temperature Rating | 221 Degrees Fahrenheit (105 Degrees Celsius) |
| Tool | CT-1002, CT-1003, CT-1123 |
| Wire Range | 14 AWG |
| Wire Range (mm ²) | 2.5 |
| Wire Strip Length (In.) | 5/8 |
| Wire Strip Length (mm) | 15.9 |
| Min. Order UOM | PC |
| Min. Order Qty. | 100 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List | <input type="button" value="e"/> |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.