



AUO Solar

e-News

Language

English

Search

Go

[About AUO](#)[Citizenship](#)[Product](#)[Technology](#)[Investor](#)[Career](#)[Support](#)[Home](#) > [Product Applications](#) > [TFT-LCD](#) > [General Display](#) > [General Display](#) > [G057VN01 V2](#)[About AUO](#)[Citizenship](#)[Product Applications](#)[Product Introduction](#)[TFT-LCD](#)

-

[LCD TV](#)

-

[PID](#)

-

[Monitor](#)

-

[Notebook PC](#)

-

[General Display](#)

-

[Mobile Device](#)

-

[DSC](#)

-

[Printer](#)

-

[Car](#)

-

[PND](#)

-

[DPF](#)[E-Paper](#)[Solar](#)[Technology](#)[Investor Relations](#)[Career](#)[Support](#)

G057VN01 V2

[General Display](#)

Model	G057VN01 V2
Size	5.7"
Resolution (pixel)	VGA (640 x 480)
Active Area	115.2 x 86.4
Pixel Pitch (mm)	0.18
Mode	TN
Number of Colors	262K
Color Saturation (%)	50
Viewing Angle (H/V)	160 / 140
Brightness (cd/m²)	700
Contrast Ratio	800 : 1
Response Time (ms)	25
Power Consumption (W)	3.34
Interface	CMOS
Supply Voltage (v)	3.3
Light Source	LED
Outline Dimension (mm)	144 x 104.6 x 12.3
Weight (g)	160
Production	Now
Remark	Reverse Scan Replaceable LED Wide Temperature

Related Links

[Technology](#)
[Awards](#)

Reference

[Contact AUO](#)