

Search Results

Evaluate

- Advertisements
- PDFHighest Perf..
- FAQ's
- Product Bulletins
- PDFDirect Buria..
- Videos
- WMV-Panduit Comp..

Design a Solution

- Catalog Cut Sheet
- PDFGCC6X61/01/ ..
- Part Drawings
- DWG-3-D cad for ..
- PDFGrounding Cr..
- DWG-2-D cad for ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDFDirect Buria..

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'GCC6X6250-1/0'


Your search criteria matched only one product, shown below

GCC6X6250-1/0



- Only a single die required to crimp each element, which speeds installation and reduces costs
- Wide range-taking ability and multi-conductor design provide flexibility with a minimum number of parts, allowing for conductor to conductor, conductor to rebar, and conductor to ground rod applications
- Designed for the enhanced crimp process using patent pending technology meets IEEE Std 837™ – 2002
- Slotted design allows quick and easy assembly of conductor to connector using Panduit cable ties, included
- Pre-applied conductive antioxidant compound ensures a high quality mechanical and electrical bond, speeding installation
- Color-coded and marked with Panduit die index numbers for proper crimp die selection
- UL 467 Listed and CSA 22.2 Certified for grounding and bonding suitable for direct burial in earth or concrete when crimped with Panduit or industry standard crimping tools and Panduit dies

- Complies with vibration tests per MIL -STD-202G (METHOD 201A)

Part Number	GCC6X62501/0
RoHS Compliancy Status	Compliant
Part Description	Grounding cross connector for #2 SOL – 250 kcmil (35– 120mm ²) and #6 SOL– 1/0 STR AWG (16 – 50mm ²) wire size.
CSA Certified	Yes
UL Listed	Yes
CE Compliant	No
Copper Conductor Size Range (B) (mm ²)	(16 – 50)
Copper Lightning Conductor Size Range (A)	65.5 – 131.5 kcmil
Ground Rod Size A (In.)	1/2 – 5/8
Ground Rod Size A (mm)	(12.7 – 15.9)
Height - A	2.12 (53.8mm)
Height - B	1.68 (42.7mm)
Length - A	1.00 (25.4mm)
Length - B	1.00 (25.4mm)
Panduit Color Code	Black
Panduit Die Index No.	PG25
Pricing Description	Ground Cross Connector for #2 SOL– 250 kcmil (35– 120mm ²) and #6 SOL– 1/0 STR AWG (16– 50mm ²)
Rebar Size A (In.)	3/8 – 1/2, #3 – #4
Rebar Size A (mm)	(9.5 – 12.7), (#10 – #13)
Width - A	1.06 (26.9mm)
Width - B	1.06 (26.9mm)
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.