

Search Results

- Evaluate
 - Advertisements
 - PDFHighest Perf..
 - FAQ's
 - Product Bulletins
 - PDFDirect Buria..
 - Videos
 - WMV-Panduit Comp..
- Design a Solution
 - Catalog Cut Sheet
 - PDFGCC6X61/01/..
 - Part Drawings
 - PDFGrounding Cr..
 - DWG-2-D cad for ..
 - DWG-3-D cad for ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor
- Install & Maintain
 - Installation Instructions
 - PDFDirect Buria..

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'GCC6X6500-250'


Your search criteria matched only one product, shown below

GCC6X6500-250



- Only a single die required to crimp each element, which speeds installation and reduces costs
- Wide range-taking ability and multi-conductor design provide flexibility with a minimum number of parts, allowing for conductor to conductor, conductor to rebar, and conductor to ground rod applications
- Designed for the enhanced crimp process using patent pending technology meets IEEE Std 837™ – 2002
- Slotted design allows quick and easy assembly of conductor to connector using Panduit cable ties, included
- Pre-applied conductive antioxidant compound ensures a high quality mechanical and electrical bond, speeding installation
- Color-coded and marked with Panduit die index numbers for proper crimp die selection
- UL 467 Listed and CSA 22.2 Certified for grounding and bonding suitable for direct burial in earth or concrete when crimped with Panduit or industry standard crimping tools and Panduit dies

• Complies with vibration tests per MIL -STD-202G (METHOD 201A)

Part Number	GCC6X6500250
RoHS Compliancy Status	Compliant
Part Description	Grounding cross connector for 250 – 500 kcmil (150– 240mm ²) and #2 SOL– 250 kcmil (35 – 120mm ²) wire size.
CSA Certified	Yes
UL Listed	Yes
CE Compliant	No
Copper Conductor Size Range (A2) (mm ²)	(150 – 240)
Copper Conductor Size Range (B) (mm ²)	(35 – 120)
Copper Lightning Conductor Size Range (A)	—
Copper Lightning Conductor Size Range (A2)	—
Ground Rod Size A (In.)	1/2 – 3/4
Ground Rod Size A (mm)	(12.7 – 19.1)
Ground Rod Size A2 (In.)	—
Ground Rod Size B2 (In.)	1/2 – 5/8
Height - A	2.48 (63.0mm)
Height - B	2.29 (58.2mm)
Length - A	1.00 (25.4mm)
Length - B	1.00 (25.4mm)
Panduit Color Code	Blue
Panduit Die Index No.	PG50
Pricing Description	Ground Cross Connector for 250– 500 kcmil (150- 240mm ²) and #2 SOL– 250 kcmil (35- 120mm ²)
Rebar Size A (In.)	5/8 – 3/4, #5 – #6
Rebar Size A (mm)	(15.9 – 19.1), (#16 – #19)
Rebar Size A2 (In.)	—
Rebar Size B2 (In.)	3/8 – 1/2, #3 – #4
Width - A	1.32 (33.5mm)
Width - B	1.16 (29.5mm)
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.