

## Eaton Series G electronic molded case circuit breaker

**GJS405032M**

**UPC:**786685000923

### **Dimensions:**

- **Height:** 7 IN
- **Length:** 3.44 IN
- **Width:** 5.34 IN

**Weight:**16 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Amperage Rating:** 50A
- **Interrupt Rating:** 85 kAIC at 240 Vac, 40 kAIC at 415 Vac, 35 kAIC at 480 Vac, 18 kAIC at 600 Vac
- **Number Of Poles:** Four-pole
- **Voltage Rating:** 600 Vac
- **Trip Type:** Electronic LSI
- **Circuit Breaker Type:** GJ
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** JG-frame
- **Protection:** 0% protected neutral pole
- **Terminals:** Line and load end caps
- **Mounting Hardware:** Metric

### **Supporting documents:**

- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Multi-wire lugs product aid](#)

- [Current limiting molded case circuit breaker module for series G, JG and CL](#)
- [Series G MCCB quick selector](#)
- [Comprehensive circuit protection for control panel applications](#)
- [High performance operating handles for Series G circuit breakers product aid](#)
- [Current limiting molded case circuit breaker module product aid](#)
- [Molded case circuit breakers providing higher levels of selective coordination product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [StrandAble terminals product aid](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [NG and ND-Frame molded case circuit breakers](#)
- [MOEM MCCB product selection guide](#)
- [Eaton Specification Sheet - GJS405032M](#)

**Certifications:**

- IEC Rated

**Product compliance:** No Data