

Eaton Series G complete molded case circuit breaker

GLH8500AAMV

UPC:782116907335

Dimensions:

- **Height:** 5.48 IN
- **Length:** 5.48 IN
- **Width:** 5.48 IN

Weight:18.7 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 500A
- **Interrupt Rating:** 100 kAIC at 240 Vac, 70 kAIC at 415 Vac, 65 kAIC at 480 Vac, 35 kAIC at 600 Vac
- **Number Of Poles:** Four-pole
- **Voltage Rating:** 600 Vac
- **Trip Type:** Adjustable thermal, adjustable magnetic
- **Circuit Breaker Type:** GL
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** LG-frame
- **Protection:** 0-60% adjustable protected neutral pole
- **Terminals:** Line and load end caps
- **Calibration:** 50°C
- **Mounting Hardware:** Metric

Supporting documents:

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)

- Application of Tap Rules to Molded Case Breaker Terminals
- StrandAble terminals product aid
- Power metering and monitoring with Modbus RTU product aid
- Current limiting molded case circuit breaker module product aid
- High performance operating handles for Series G circuit breakers product aid
- Comprehensive circuit protection for control panel applications
- Molded case circuit breakers providing higher levels of selective coordination product aid
- Current limiting molded case circuit breaker module for series G, JG and CL
- Circuit breaker motor operators product aid
- Motor protection circuit breakers product aid
- Series G MCCB quick selector
- Multi-wire lugs product aid
- Plug-in adapters for molded case circuit breakers product aid
- Eatons Volume 4-Circuit Protection
- Molded case circuit breakers
- Breaker service centers
- NG and ND-Frame molded case circuit breakers
- Eaton Specification Sheet - GLH8500AAMV
- MOEM MCCB product selection guide

Certifications:

- IEC Rated

Product compliance: No Data