Note: This datasheet may be out of date.
Please download the latest datasheet of GR443QR73D392KW01# from the official website of Murata Manufacturing Co., Ltd.
http://www.murata.com/en/products/productdetail?partno=GR443QR73D392KW01%23

GR443QR73D392KW01#

"#" indicates a package specification code.

In Production | General | RoHS | REACH | 125 °C max. | Reflow OK

< List of part numbers with package codes >
GR443QR73D392KW01K GR443QR73D392KW01L

Appearance & Shape



References

Packaging	Specifications	Minimum Order Quantity
K	330Embossed Tape	4000
L	180Embossed Tape	1000

Mass (typ.)	
1 piece	110mg

Notices

LAN/DC-DC Converter Primary-Secondary Couplings only

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Note: This datasheet may be out of date.
Please download the latest datasheet of GR443QR73D392KW01# from the official website of Murata Manufacturing Co., Ltd.
http://www.murata.com/en/products/productdetail?partno=GR443QR73D392KW01%23

GR443QR73D392KW01#

"#" indicates a package specification code.

Specifications

Length	4.5±0.4mm
Width	3.2±0.3mm
Thickness	1.5+0/-0.3mm
Capacitance	3900pF ±10%
Distance between external terminals g	2.5mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55°C to 125°C
Rated Voltage	2000Vdc
Size code in inch(mm)	1812 (4532M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.