

GRM32ER71A476ME15#

“ # ” indicates a package specification code.


Recommended

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM32ER71A476ME15L , GRM32ER71A476ME15K

Shape

		
L size		3.2 ±0.3mm
W size		2.5 ±0.2mm
T size		2.5 ±0.2mm
External terminal width e		0.3mm min.
Distance between external terminals g		1.0mm min.
Size code in mm(inch)		3225 (1210)

Specifications

Capacitance	47μF ±20%
Rated voltage	10Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 125℃
Operating temperature range	-55 to 125℃

References

Packaging	Specifications	Minimum quantity
L	φ 180mm Embossed taping	1000
K	φ 330mm Embossed taping	4000


	Mass (typ.)
1 piece	110mg
φ 180mm Reel	168g

 Attention


1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Frequency characteristics (ESR, Impedance)




S parameter (Smith chart S11)




DC bias characteristics




AC voltage characteristics



Capacitance - temperature characteristics



Calorific property by ripple current



This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.