

Product availability: Stock - Normally stocked in distribution facility



### Main

|                              |   |
|------------------------------|---|
| Product                      | Single Throw Safety Switch                            |
| Current Rating               | 100 A   |
| Certifications               | UL listed file E2875                                  |
| Enclosure Rating             | NEMA 3R/12 galvanized steel                           |
| Factory Installed Neutral    | None  |
| Disconnect Type              | Fusible disconnect                                    |
| Short Circuit Current Rating | 10 KA H or K<br>200 kA R, J or L                      |
| Mounting Type                | Surface   |
| Number of Poles              | 2   |
| Electrical Connection        | Lugs  |
| Duty Rating                  | Heavy duty  |
| Voltage Rating               | 250 V DC<br>240 V AC                                  |
| Wire Size                    | AWG 12...AWG 1/0 aluminium<br>AWG 14...AWG 1/0 copper |

### Complementary

|                   |  |
|-------------------|--|
| Width             | 228.60 mm (9 in)   |
| Height            | 520.70 mm (20.5 in)  |
| Depth             | 177.80 mm (7 in)   |
| Tightening torque | 5.65 N.M (50 lbf.in) AWG 1...AWG 3/0)<br>5.08 N.M (45 lbf.in) AWG 6...AWG 4)<br>4.52 N.M (40 lbf.in) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8)<br>3.95 N.m (35 lbf.in) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10) |

### Ordering and shipping details

|                     |                                  |
|---------------------|----------------------------------|
| Category            | 00113 - H&HU SW,2&3P,N12,30-200A |
| Discount Schedule   | DE1                              |
| GTIN                | 00785901478140                   |
| Package weight(Lbs) | 8.97 kg (19.78 lb(US))           |
| Returnability       | Yes                              |
| Country of origin   | US                               |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.