


[> PN Search](#)
[Home page](#)
[Product quick search](#)

P/N Search

[Product type search](#)
[Alphabetical list](#)
[Connection type](#)
[Markets / Applications](#)
[Product finder](#)
[Literature](#)
[Services](#)
[Contact us](#)
[Registered users](#)
[Forgot password ?](#)
[Register now](#)
Millipacs™
 HM2P09PDE1U0N9


FCI brings you more

 [Contact our sales/technical support](#)
 [Sample request](#)
 [Price request](#)
 [Check distributor stock](#)

[> Customer Drawing](#)
[> Product Specification](#)
[> 3D Model](#)

Not Available

Not Available

www.foehrenbach.be
[Americas](#)
[Asia Pacific](#)

Features Selected

Product Type	Header
Contact Finish	Level 2 (0.8 microns Au)
Series	Module type C
Gender	Header
Orientation	Straight
#ofRows	5
# of Positions	55
Tail Lengths	Short Tails (3.7mm)
PCB Mounting	Press-fit
Shielded?	no

Other Properties

Housing Material	High Temperature Thermoplastic (UL94 V-0)
Contact Base Material	Phosphor Bronze
Operating Temperature	-55°C to +125°C
Signal Contact Current Rating	1.5 A @ 20°C, 1.0 A @ 70°C
Signal Contact Test Voltage (Fully Loaded)	750 Vrms
Signal Contact, Contact Resistance	20 milli ohms max
Signal Contact Insulation Resistance	10000 mega ohms min
Signal Contact Mating Force	0.75 N max per contact pair
Signal Contact Withdrawal Force	0.15 N min per contact pair
Signal Contact Hertz Stress	200 Kpsi min
Contact Levels	Refer to Customer Drawing
Signal Contact Normal Force	0.75 N min (EOL)
Approvals and Certification	UL and CSA Certified