

# Product data sheet

## Characteristics

# HOM816L125PRB

Homeline, LC, 125 A, 120/240 V, 1 PH, MLO, PoN, 8 SP, N3R, surf



Product availability: Stock - Normally stocked in distribution facility



### Main

Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	8
Number of circuits	16
Enclosure Rating	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Lugs

### Complementary

Short-circuit current	10 kA
Number of Tandem Breakers	8
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 6...AWG 2/0 aluminium AWG 6...AWG 1 copper
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	3R
Height	19.09 in (485 mm)
Width	14.76 in (375 mm)
Depth	4.53 in (115 mm)
Tightening torque	5.65 N.M (50 lbf.in) AWG 6...AWG 1) 5.65 N.m (50 lbf.in) AWG 6...AWG 2/0)

### Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL E-6294

### Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901973997
Package weight(Lbs)	9.25 kg (20.4 lb(US))
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations