

# HOMT1515240CP

## MINIATURE CIRCUIT BREAKER 120/240V 15A

Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A 40 A
Certifications	UL listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P 2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 14...AWG 6 copper)1 AWG 12...AWG 6 aluminium)1 AWG 12...AWG 8 aluminium)1
Type of packing	Consumer packaging

### Complementary

Height	79.50 mm (3.13 in)
Width	50.80 mm (2 in)
Depth	75.69 mm (2.98 in)
Tightening torque	0.00...0.02 In <sup>2</sup> (2.5...10 mm <sup>2</sup> ) AWG 14...AWG 6) 40.71 Lbf.in (4.6 N.m) 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> ) AWG 14...AWG 6) 0.00...0.03 In <sup>2</sup> (2.5...20 mm <sup>2</sup> ) AWG 14...AWG 2) 40.71 lbf.in (4.6 N.m) 0.00...0.03 in <sup>2</sup> (2.5...20 mm <sup>2</sup> ) AWG 14...AWG 2)

### Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

### Ordering and shipping details

Category	00046 - HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	00785901395829
Package weight(Lbs)	0.41 kg (0.91 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty	18 months
----------	-----------

---