




HPM-08-01-T-S-VS



HPW-06-04-T-S-350-150

HPM-04-01-T-S

(5.08 mm) .200"

HPM, HPW SERIES

POWER HEADERS & BOARD STACKERS

HPM & HPW Mates with:
HPF

SPECIFICATIONS

For complete specifications see www.samtec.com?HPM or www.samtec.com?HPW

Insulator Material:
HPM = Glass Filled Polyester (Through-hole),
Natural Liquid Crystal Polymer (Surface Mount)
HPW = Liquid Crystal Polymer
Terminal Material:
Copper Alloy
Plating:
Sn over 50 μm (1.27 μm) Ni
Operating Temp Range:
-55 °C to +105 °C
Voltage Rating:
HPM = 850 VAC/1200 VDC
Standard Creepage:
(3.94 mm) .155"
Standard Clearance:
(3.94 mm) .155"
RoHS Compliant:
Yes

PROCESSING


Lead-Free Solderable:
HPM Surface Mount = Yes
HPM TH & RA = Wave only
HPW = Yes
SMT Lead Coplanarity:
HPM = (0.20 mm)
.008" max (02-15)*
HPM = (0.25 mm)
.010" max (16-20)*
HPW = (0.20 mm) .008" max*
*(.004" stencil solution may be available; contact IPG@samtec.com)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality




Note:
Some lengths, styles and options are non-standard, non-returnable.





HPF/HPM	
PINS	CURRENT RATING (PER CONTACT)
1	16.6 A
2	14.4 A
3	13.2 A
4	12.7 A
20	8.9 A

Specify LEAD STYLE from chart below.



LEAD STYLE	A	B	C	D	E	F	G
-01	(4.57) .180	(11.94) .470				(10.72) .422	(8.64) .340
-02	(4.57) .180	(13.21) .520	(2.54) .100	(4.57) .180	(8.08) .318	(12.24) .482	(8.38) .330
-04	(4.09) .161	(21.06) .829	(4.95) .195	(3.96) .156	(13.82) .544		
-05	(4.57) .180	(3.81) .150					

CREEPAGE AND CLEARANCE



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.