



BURNDY Catalog Number
UPC Number
Description
Status

HSIC10500FR
 7818102665577
 5/PK, 1/0-500, HEAVYWALL
 Active

Web Use
 BURNDY Product Line

Dimensional

Wall Thickness - Recovery	0.120
Flex Wire Range	#1-313.1 kcmil
Dimension (Max Before Shrink)	1.10
Expansion Length	4.0
Length - Recovery	3.00
Wall Thickness - Exp	0.039
Recovery - Max ID	0.35

General

Product Description Heavy Wall Cross-Linked Black Polyolefin Heat Shrinkable End Cap, 1/0-500 kcmil Code, #1-313 kcmil Flex, 600 V, Fire Retardant

Approvals / Certifications

UL Listed	Y
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Physical

Shrink Ratio	3:1
Color	Black
Code Wire Range	1/0-500 kcmil

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175