



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'HSTTPN100-CC'

Your search criteria matched only one product, shown below

HSTTPN100-CC



- Low shrink temperature (store below 90° F) to speed installation
  - Crystal clear material ensures easy to read labels and splice inspections
  - Highly flame retardant product manufactured from a material that is rated UL224 VW -1
  - Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Meets Mil Spec AMS-DTL-23053/2 Class 2.

|                                        |                                                          |
|----------------------------------------|----------------------------------------------------------|
| Part Number                            | HSTTPN100CC                                              |
| RoHS Compliancy Status                 | Compliant                                                |
| Part Description                       | Crystal Clear PVC Heat Shrink                            |
| Material                               | Highly flame retardant non cross-linked PVC <sup>^</sup> |
| Color                                  | Clear                                                    |
| Military Specification                 | AMS-DTL-23053/2 Class 2                                  |
| Continuous Use Temperature Range       | -31°F to 221°F<br>(-35°C to 105°C)                       |
| Length Per Reel (ft.)                  | 100                                                      |
| Length Per Reel (m)                    | 30.5                                                     |
| Max. Recovered I.D. (In.)              | .50                                                      |
| Max. Recovered I.D. (mm)               | 12.7                                                     |
| Min. Expanded I.D. (In.)               | 1.0                                                      |
| Min. Expanded I.D. (mm)                | 25.4                                                     |
| Nominal Diameter (In.)                 | 1                                                        |
| Nominal Diameter (mm)                  | 25.4                                                     |
| Nominal I.D. (In.)                     | 1.0                                                      |
| Nominal I.D. (mm)                      | 25.4                                                     |
| Nominal Recovered Wall Thickness (In.) | .04                                                      |
| Nominal Recovered Wall Thickness (mm)  | 1.0                                                      |
| Pricing Description                    | 1" (25.4mm) PVC Heat Shrink Clear                        |
| Temperature Range                      | -31°F to 221°F (-35°C to 105°C)                          |
| Min. Order UOM                         | RL                                                       |
| Min. Order Qty.                        | 1                                                        |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>                           |
| Add to Favorite Product List           |                                                          |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.