

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'HSTTVA150-48-5'


Your search criteria matched only one product, shown below

HSTTVA15048-5



Dual Wall Polyolefin DAMP-SHRINK™ Heat Shrink Tubing in 4 ft (1.2M) Pieces

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- For use when a flexible adhesive lined tubing is needed
- Material Type: Polyolefin Cross-Linked with adhesive
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage Rating: 600V
- Mil Spec: AMSDTL-23053/4 Class 2

Part Number	HSTTVA150-48-5
RoHS Compliancy Status	Compliant
Part Description	Dual Wall Adhesive Lined Thin Wall Heat Shrink (UL224 VW)
Material	Polyolefin Cross-linked with adhesive
Color	Black
Military Specification	AMS-DTL-23053/4 Class 2
Length (ft.)	4
Length (m)	1.2
Flammability Rating	Outer Wall Flame Retardant
Max. Recovered I.D. (In.)	.750
Max. Recovered I.D. (mm)	19.0
Min. Expanded I.D. (In.)	1.50
Min. Expanded I.D. (mm)	38.1
Nominal Diameter (In.)	1.50
Nominal Diameter (mm)	38.1
Nominal Recovered Wall Thickness (In.)	.049
Nominal Recovered Wall Thickness (mm)	1.2
Pricing Description	Heat Shrink Thin, Adhesive, 1.50"(38.1mm) Dia
Shrink Ratio	2:1
Temperature Range	-67°F to 230°F
Min. Order UOM	PC
Min. Order Qty.	5
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.