



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Network number of phases	3 phases
Number of Poles	3
Current Rating	30 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12 galvanized steel
Motor power hp	5 Hp at 240 V AC 50...60 Hz for 1 phase motors 10 Hp at 240 V AC 50...60 Hz for 3 phases motors 7.5 Hp at 480 V AC 50...60 Hz for 1 phase motors 20 Hp at 480 V AC 50...60 Hz for 3 phases motors 10 Hp at 600 V AC 50...60 Hz for 1 phase motors 30 Hp at 600 V AC 50...60 Hz for 3 phases motors 5 Hp at 250 V DC 15 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Tightening torque	5.08 N.M for 13.3 mm ² (AWG 6) 4.52 N.M for 8.367 mm ² (AWG 8) 3.95 N.m for 2.06...5.261 mm ² (AWG 14...AWG 10)
Depth	125.98 mm
Width	191.77 mm
Height	370.84 mm
Net weight	5 kg

Environment

Certifications	UL listed file E2875
----------------	----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.97 cm
Package 1 Width	19.558 cm
Package 1 Length	44.45 cm
Package 1 Weight	4.513 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	96
Package 2 Height	116.84 cm
Package 2 Width	101.6 cm

Package 2 Length	121.92 cm
Package 2 Weight	444.52 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------