

4 Port USB to RS232 Serial DB9 Adapter Hub

Product ID: ICUSB2324



This 4 Port USB to RS232 Serial Hub lets you connect up to four RS232 serial devices to your Mac or PC laptop or desktop computer through a single USB port, as though the computer offered built-on DB9M serial connectors.

The RS232 Serial Hub is compactly designed to preserve valuable workspace, and is bus-powered to eliminate the need for an external power adapter.

A cost-effective solution that bridges the compatibility gap between modern USB-capable computers and legacy RS232 serial peripherals, this dependable USB/RS232 Serial Adapter hub is backed by StarTech.com's Lifetime Warranty.

Certifications, Reports and Compatibility



Applications

- Connect modems, digitizer tablets, mice, bar code scanners, GPS receivers, ISDN terminal adapters, mobile phones, scanners, UPSes and POS equipment to your system
- Connect and program LED and Digital signage boards with serial communication ports

Features

- Bus powered, no external power adapter required
- Easy Plug-and-Play installation
- Fully compliant with USB 1.1 specifications and compatible with USB 2.0
- Provides you with four additional RS232 serial ports

| | | |
|-------------------------------------|-------------------------------|---|
| Hardware | Warranty | Lifetime |
| | Bus Type | USB 2.0 |
| | Chipset ID | FTDI - FT232RL |
| | Industry Standards | RS232 |
| | | USB 1.1 |
| | Interface | Serial |
| | Port Style | External Hub |
| | Ports | 4 |
| Performance | FIFO | 256 Bytes |
| | Max Baud Rate | 921.6 Kbps |
| | Serial Protocol | RS-232 |
| Connector(s) | Connector Type(s) | 1 - USB Type-A (4 pin) USB 2.0 Male |
| | External Ports | 4 - DB-9 (9 pin, D-Sub) Male |
| Software | OS Compatibility | Windows® CE (4.2, 5.0, 6.0), XP Embedded, 98SE, 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS® 10.6 to 10.15 Linux 2.4.x to 4.11.x <i>LTS Versions only</i> |
| Special Notes / Requirements | System and Cable Requirements | One free USB port |
| Power | Power Consumption (In Watts) | 1 ~ 1.5W |
| Environmental | Humidity | 5~95% RH |
| | Operating Temperature | 0°C to 55°C (32°F to 131°F) |
| | Storage Temperature | -20 to 85°C (-4 to 185°F) |
| Physical Characteristics | Cable Length | 6 ft [1.8 m] |
| | Material | Plastic |
| | Product Height | 1 in [2.6 cm] |
| | Product Length | 5.9 in [15 cm] |
| | Product Width | 2.6 in [66.5 mm] |
| | Weight of Product | 6.2 oz [175 g] |
| Packaging Information | Package Height | 2.1 in [53 mm] |
| | Package Length | 8.7 in [22 cm] |

| | | |
|--------------------------|---------------------------|---|
| | Package Width | 5.9 in [15 cm] |
| | Shipping (Package) Weight | 13.3 oz [378 g] |
| What's in the Box | Included in Package | 1 - 4 Port Serial Hub 1 - USB Cable 1 - Mounting Bracket 1 - Driver CD 1 - Instruction Manual |

Product appearance and specifications are subject to change without notice.