

## 6 ft. (1.8 m) Cisco USB Console Cable - USB to RJ45

Product ID: ICUSBROLLOVR



This Cisco USB console cable offers a reliable connection from your desktop or laptop to networking equipment that features a console port.

### Compatible USB Connection

Create a direct connection from the USB 2.0 port on your computer or laptop to the RJ45 console port on your router, server, firewall or switch. This Cisco rollover cable is compatible with most routers, including Cisco, Juniper, Ubiquiti or TP-Link, providing an easy connection for programming your networking equipment from your Windows, Mac or Linux computer.

### High-Quality Design

Expertly designed and constructed with only the highest quality materials, this USB to Ethernet cable provides maximum dependability, supporting data transfer rates up to 460Kbps. It also provides a reliable and hassle-free connection without the need for additional adapters or external power.

ICUSBROLLOVR is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Connect a computer terminal to a router console port
- Configure your networking equipment through the USB port on your laptop or desktop computer
- Connect laptops to compatible routers, servers or firewalls

### Features

- Directly connect a USB-equipped laptop or desktop to a router console, without the need for an adapter
- Supports connections to network devices that feature a console port
- Maximum compatibility with Cisco®, Juniper®, Ubiquiti® or TP-Link® routers
- Supports a direct USB console connection, with no additional adapters
- Constructed of high-quality materials, supports transfer rates of up to 460Kbps

|                                     |                               |                                                                                                                                                   |
|-------------------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hardware</b>                     | Warranty                      | 2 Years                                                                                                                                           |
|                                     | Bus Type                      | USB 2.0                                                                                                                                           |
|                                     | Cable Jacket Type             | PVC - Polyvinyl Chloride                                                                                                                          |
|                                     | Chipset ID                    | Prolific PL2303HxD                                                                                                                                |
|                                     | Industry Standards            | USB 1.1/2.0, RS-232                                                                                                                               |
|                                     | Port Style                    | Cable Adapters                                                                                                                                    |
|                                     | Ports                         | 1                                                                                                                                                 |
| <b>Performance</b>                  | Data Bits                     | 5, 6, 7, 8                                                                                                                                        |
|                                     | FIFO                          | 512 Bytes                                                                                                                                         |
|                                     | Max Baud Rate                 | 460.8 Kbps                                                                                                                                        |
|                                     | Parity                        | Odd, Even, Mark, Space, or None                                                                                                                   |
|                                     | Stop Bits                     | 1, 1.5, 2                                                                                                                                         |
|                                     | Supported Protocols           | RS-232                                                                                                                                            |
| <b>Connector(s)</b>                 | Connector A                   | 1 - USB Type-A (4 pin) USB 2.0 Male                                                                                                               |
|                                     | Connector B                   | 1 - RJ-45 Male                                                                                                                                    |
| <b>Software</b>                     | OS Compatibility              | Windows® 7, 8, 8.1, 10<br>Windows Server® 2008 R2, 2012, 2012 R2, 2016<br>Mac OS® 10.6 to 10.15<br>Linux 2.4.31 to 4.11.x <i>LTS version only</i> |
| <b>Special Notes / Requirements</b> | System and Cable Requirements | One available USB 1.1 (or above) port                                                                                                             |
| <b>Power</b>                        | Power Source                  | Bus Powered                                                                                                                                       |
| <b>Environmental</b>                | Humidity                      | 20~80% RH                                                                                                                                         |
|                                     | Operating Temperature         | 0°C to 70°C (32°F to 158°F)                                                                                                                       |
|                                     | Storage Temperature           | -20°C to 80°C (-4°F to 176°F)                                                                                                                     |
| <b>Physical Characteristics</b>     | Cable Length                  | 6 ft [1.8 m]                                                                                                                                      |
|                                     | Color                         | Black                                                                                                                                             |
|                                     | Material                      | Plastic                                                                                                                                           |
|                                     | Product Height                | 0.4 in [1.1 cm]                                                                                                                                   |
|                                     | Product Length                | 6 ft [1.8 m]                                                                                                                                      |
|                                     | Product Width                 | 0.9 in [23.4 mm]                                                                                                                                  |
|                                     | Weight of Product             | 1.4 oz [40 g]                                                                                                                                     |

|                              |                           |                                |
|------------------------------|---------------------------|--------------------------------|
|                              | Wire Gauge                | 28 AWG                         |
| <b>Packaging Information</b> | Package Height            | 1.2 in [30 mm]                 |
|                              | Package Length            | 6.7 in [17 cm]                 |
|                              | Package Width             | 5.6 in [14.2 cm]               |
|                              | Shipping (Package) Weight | 3.5 oz [98 g]                  |
| <b>What's in the Box</b>     | Included in Package       | 1 - USB to RJ45 Rollover Cable |
|                              |                           | 1 - Quick-Start Guide          |
|                              | Connector Plating         | Nickel                         |

Product appearance and specifications are subject to change without notice.