



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact J |
| Trip unit technology | Thermal-magnetic |
| Breaking capacity code | D |

Complementary

| | |
|--------------------------------|--|
| Line Rated Current | 175 A |
| Number of poles | 3 |
| Poles description | 3P |
| Breaking capacity | 25 KA 240 V AC 18 KA 480 V AC 14 KA 600 V AC 20 kA 250 V DC |
| [Ue] rated operational voltage | 600 V AC 250 V DC |
| Continuous current rating | 80 % |
| Mounting mode | Unit mount |
| Electrical connection | Busbar connection line Busbar connection load |
| Magnetic hold current | 875 A |
| Magnetic tripping current | 1750 A |
| Height | 191.01 mm (7.52 in) |
| Width | 104.65 mm (4.12 in) |
| Depth | 127.00 mm (5 in) |
| Tightening torque | 230.12 lbf.in (26 N.m) 0.15...0.29 in ² (95...185 mm ²) AWG 3/0...350 kcmil |

Environment

| | |
|---------------------------------------|--------------------------------------|
| Product certifications | CE UL listed IEC CCC CSA |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 01110-HD,JD UNIT MT BREAKER/SWITCH |
| Discount Schedule | DE2 |
| GTIN | 00785901834397 |
| Package weight(Lbs) | 4.50 lb(US) (2.041 kg) |
| Returnability | Yes |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|